

Report No.: 18300RC20366801

Test Report

Client Name : EcoFlow Inc.

Plant A202, Founder Technology Industrial

Client Address : Park, Shiyan Sub-district, Bao'an District

Shenzhen, Guangdong 518000 China

Product Name : Portable Power Station

Report Date : Sept. 23, 2022

Shenzhen Anbotek Compliance Laboratory Limited
Approved







Report No.: 18300RC20366801 Date: Sept. 23, 2022 Page 1 of 7

Applicant EcoFlow Inc.

Address Plant A202, Founder Technology Industrial Park, Shiyan Sub-district,

Bao'an District Shenzhen, Guangdong 518000 China

The submitted sample and sample information was/were submitted and identified by/on the behalf

of the client

Sample Name Portable Power Station

Test Model No. **EFR600**

Manufacturer EcoFlow Inc.

Trade Mark

ECOFLOU

Sept. 07, 2022 Sample Received Date

Testing Period Sept. 07, 2022 to Sept. 20, 2022

Test Requested As specified by client, to assess the reuse/recycle/recovery of the

submitted sample under article 11 and Annex V of Directive

2012/19/EU.

Conclusion When tested as specified, the results shown on the report meet the

requirements of the Reuse/Recycling/Recovery Rate of Directive


2012/19/EU released on EU Official Journal (OJ)

Test Result(s): Please refer to the following page(s).

Edited by Wei VIA XIII

Reviewed by OlnNa

Authorized Signatory









Report No.: 18300RC20366801 Date: Sept. 23, 2022 Page 2 of 7

1. Product Description

Product Name	Portable Power Station
Product Model	EFR600
Product Weight	3672.0g(including battery: 1416.0g)
Product Size	24.3cm×21.3cm×14.5cm
Category under the WEEE directive	SMALL EQUIPMENT

Product Photo







2. Result of Reuse/Recycling/Recovery Assessments

Reuse/Recycling/Recovery	Reuse/Recycling Rate (%)	Recovery Rate (%)		
Reuse/Recycling/Recovery Target of Products Under WEEE Directive	55	mbotek A75 tek Anb		
Result of Assessment	100 88.9 Million 100 100 100 100 100 100 100 100 100 10	88.9		
WEEE Compliance	Pass	Pass		

Remark: Battery was not within the scope of WEEE, it should be complied with the Battery Directive 2006/66/EC.

3. Appearance of the Product











Report No.: 18300RC20366801 Date: Sept. 23, 2022 Page 3 of 7

4. Disassembly Assessment

4.1 Disassembly Procedure

The product is disassembled into different parts and grouped by the type of material sharing common characteristic(such as plastic, metal, glass) based on the treatment requirements as set out in the WEEE Directive, followed by the current state of the art of recycling and recovery technology. In addition, the recycling is subject to the economic feasibility, disassembly tools, only bigger parts that can be easily separated are included in the recycling and reuse calculation. Other parts, respectively materials that cannot be separated by e.g. standard tools are classified as either unspecified materials or distributed to the relative waste fraction is expected with recovery rate.

4.2 Disassembly Tools

The disassembly tools used for this product show as following:

Anbotek	Disassembly Tool	Auprijek	Anbotek	Picture	nbotek Anbo	botek
20010	tek Anbotek Anbo	Hek Hipo.	h.	V/S _J /		Anbor
		pole And	potek p			
		Anbotek An	Anborek	n-title	aboten	
		"pote"				
		vapole.		- nD-		
		ek boter	Anbore			
	ek Anbotek Anbot	-0.7			potek	
		You You	oter P	o const	Anbotek	
otek An	Anbotek Anbotek	Anbotek	Anbotek		Anbotek	
ole.	tek abotes	br.	poier	~ 40°	ale above	16
		Aupotek *ek			do No	
	All Aport	Sie Viu	k Anbo'	11		
	Auropea	ooter And			Anbotek	
		Anbotek Anb		The Land	Aupotek	
Vi.	notek Anbore	P. P.	abotek	V07	Aupo.	

4.3 Connection Technique

	N. Sterr	VU/2			Dr.		
	Snap : 0	W.	Screw :51		- Otok	Glue: 0	
100	Ando	apore	ble	hotek	AUDO	rek	(upo)



AB-RHS-03-b





Report No.: 18300RC20366801 Date: Sept. 23, 2022 Page 4 of 7

4.4 Disassembly Time

30 minute and 30 seconds

4.5 Disassembly Tree



5. Selective Treatment for Materials and Components

According to Article 8(2) and the Annex VII of the WEEE Directive, this product contains components and materials items are described in the following table.

Component/Material	Photo No.	Size/Model	Quantity	Weight (g)	
PCB	B4	21.5cm×13.5cm	atek5 Naoti	729.0	



AB-RHS-03-b
Hotline
400-003-0500
www.anbotek.com.cn





Report No.: 18300RC20366801 Date: Sept. 23, 2022 Page 5 of 7

6. Material Recycling Information

6.1 Material Reuse/Recycling and Recovery Table

Photo No.	Component / Material Composition	Weight (g)	Percent Weight (%)	Reuse / Recycling Rate(%)	Energy Recovery Rate(%)	Recovery Rate(%)
B1	Plastic Parts	1121.0	49.7	44.7	Ago	44.7
B2	Cable	173.0	7.7	6.5	K Anbo	6.5
B3	Metal Parts	223.0	9.9	9.9	otek Anbo	9.9
B4	PCB	729.0	32.3	27.5	otek!	27.5
B5	Rubber	10.0	0.4	0.3	rup.	0.3
otek Ant	Lose rate	0.0	0.0	abbiek	Aupo	M. Make
hotek	Total	2256.0	100.0	88.9	0.0	88.9

Note: Plastic containing brominated flame retardants is not assessed in the list

6.2 Reuse/Recycling and Recovery Rate Calculation

·Calculat	ion Method	Anbotek Anbo	
Product total weight	Anbotek Anbo	a (g)	boro
Weight of components, sub-assemblies and consu- which are reused for their original purpose or recyc	VUD	b (g)	Anbotek
Weight of materials or components where energy is recovered through incineration.	s Andotek Ar	c (g)	Anbote
Reuse / Recycling Rate	potek Anbore	b/a *100 (%)	Sr. Vup
Recovery Rate	botek Anbotes	(b+c)/a *100 (%)	oo'ek

7. ANNEX VII of WEEE Directive (2012/19/EU)

Selective treatment for materials and components of waste electrical and electronic equipment referred to in Article 8(2)

As a minimum the following substances, mixtures and components have to be removed from any separately collected WEEE

- —polychlorinated biphenyls (PCB) containing capacitors in accordance with Council Directive 96/59/EC of 16 September 1996 on the disposal of polychlorinated biphenyls and polychlorinated terphenyls (PCB/PCT),
- mercury containing components, such as switches or backlighting lamps,
- —batteries,
- printed circuit boards of mobile phones generally, and of other devices if the surface of the printed circuit board is greater than 10 square centimetres,

Shenzhen Anbotek Compliance Laboratory Limited







Report No.: 18300RC20366801 Date: Sept. 23, 2022 Page 6 of 7

- —toner cartridges, liquid and paste, as well as colour toner,
- —plastic containing brominated flame retardants,
- asbestos waste and components which contain asbestos,
- —cathode ray tubes,
- —chlorofluorocarbons (CFC), hydrochlorofluorocarbons (HCFC) or hydrofluorocarbons (HFC), hydrocarbons (HC),
- -gas discharge lamps,
- —liquid crystal displays (together with their casing where appropriate) of a surface greater than 100 square centimeters and all those back-lighted with gas discharge lamps,
- -external electric cables,
- —components containing refractory ceramic fibres as described in Commission Directive 97/69/EC of 5 December 1997 adapting to technical progress for the 23rd time Council Directive 67/548/EEC on the approximation of the laws, regulations and administrative provisions relating to the classification, packaging and labelling of dangerous substances,
- —components containing radioactive substances with the exception of components that are below the exemption thresholds set in Article 3 of and Annex I to Council Directive 96/29/Euratom of 13 May 1996 laying down basic safety standards for the protection of the health of workers and the general public against the dangers arising from ionizing radiation,
- —electrolyte capacitors containing substances of concern (height > 25 mm, diameter > 25 mm or proportionately similar volume). These substances, mixtures and components shall be disposed of or recovered in compliance with Directive 2008/98/EC.

8. Recommendations for WEEE Directive Compliance

- (1) To make the product comply with the reuse/recycling/recovery target required under WEEE Directive (2012/19/EU) and other EU waste regulation, the applicant company should consider the product they design can be easily reused and recycled by selecting recyclable materials and components.
- (2) To make the product easily dismantled, less the disassembling time, the applicant company should design the product for easy disassembly by choosing easy separate techniques, avoiding the utilizing embedded components, designing the separable procedure.
- (3) The product should be subjected to the RoHS Directive (2011/65/EU), restricting using hazardous substance. In addition, the materials selected to design should consider the dangerous substance regulated or list under other environmental specifications, as Regulation (EC) 1907/2006(REACH), 67/548/EEC, etc.
- (4) In case that a product have new design, or employ materials or components, then the product should

Hotline 400-003-0500 www.anbotek.com.cn

AB-RHS-03-b





Report No.: 18300RC20366801 Date: Sept. 23, 2022 Page 7 of 7

need to be reassessed and retested in accordance with the WEEE Directive for reuse/recycle/recycling target and RoHS for restricted substances requirement.

(5) The applicant company should take attention to the future possible update concerning the WEEE Directive and related requirement.

***** End of Report *****

The test report is effective only with both signature and specialized stamp. The result(s) shown in this report refer only to the sample(s) tested. Without written approval of Anbotek, this report can't be reproduced except in full.

