

Multy OUTDOOR

Model	C&H		CHML-U14RK2	CHML-U18RK2	CHML-U21RK3	CHML-U24RK3	CHML-U28RK4
Capacity	Cooling	W	4100	5200	6100	7100	8000
	Heating	W	4400	5400	6500	8500	9500
Power supply			~/1ph/220-240/50	~/1ph/220-240/50	~/1ph/220-240/50	~/1ph/220-240/50	~/1ph/220-240/50
Nominal capacity	Cooling	W	1200	1450	1740	1950	2300
	heating	W	1180	1300	1600	2200	2650
Working current	Cooling	A	5,32	6,43	7,72	8,65	10,20
	heating	A	4,53	5,77	7,10	9,76	11,76
Energy efficiency	EER (cooling)	W/W	3,10	3,59	3,51	3,64	3,48
	C.O.P. (heat)	W/W	4,00	4,15	4,06	3,86	3,58
SEER	SEER (cooling)		6,1	6,1	6,1	6,1	6,3
	SCOP (heating)		4	4,6	4,6	4	4
Energy class	cooling/heating		A++/A+	A++/A+	A++/A+	A++/A+	A++/A+
Working temperature range	Cooling	°C	-15~43	-15~43	-15~43	-15~43	-15~43
	Heating	°C	-20~24	-20~24	-20~24	-20~24	-20~24
Dimensions	(width/height/dep)	mm	899x596x378	899x596x378	963x396x700	1001x427x790	1001x427x790
Packing dimensions	(width/height/dep)	mm	948x420x645	948x420x645	1029x458x750	1083x488x855	1083x488x855
Weight	netto/brutto	kg	43/46	43/46	55/60	68/73	52/57
Compressor	type		rotary	rotary	rotary	rotary	rotary
	manufacturer		Zhunai Landa	Zhunai	Zhunai	Zhunai	Zhunai
refrigerant	R32	g	1050	1050	1600	1800	1700

